

H.265 CCTV Hybrid Network DVR

KMH 25系列



MAIN FEATURES

- Up to 4CH DTV Max.8MP 30/25 fps
- Up to 5MP (2592 x 1944) CCTV camera supported
- Support TVI, AHD, CVI analog camera and IP Camera
- Support OSD setting over coaxial (UTC)
- Support IP camera with Onvif Profile protocol (V2.4)
- Cross device function for redundant recording
- Ideal for project bid, public place like airport, bank, and administration
- Excellent picture quality



iCATCH

FC CE RoHS

www.icatchinc.com

KMH x25

型號			KMH-0425EU-K Plus	KMH-0425MU-K Plus	KMH-0825EU-K Plus	KMH-0825MU-K Plus	KMH-1625EU-K Plus
攝影機輸入			4CH (Analog video + IP video) , CH1 can support DTV mode		8CH (Analog video + IP video) , CH1-2 can support DTV mode		16CH (Analog video + IP video) , CH1-4 can support DTV mode
外殼			K	K	K	K	K
DTV即時輸入			1ch DTV Max.8MP30/25fps		2ch DTV Max.8MP30/25fps		4ch DTV Max.8MP30/25fps
類比即時輸入			TVI/AHD/CVI :8MP , 5MP , (4MP , 3MP , 1080P , 720P , 960H/D1) @30/25fps				
影像	網路輸入	頻寬 (允許一人遙控登入)	Max. 50Mbps (Max. Main stream: 6 Mbps + Sub stream: 1 Mbps per channel)				Max. 115Mbps (Max. Main stream: 6Mbps + Sub stream: 1Mbps per channel)
		單一即時與回放頻道 (無類比攝影機輸入)	Max. Up to 8 MP resolution (ONVIF 2.4)				
		多重即時與回放頻道 (無類比攝影機輸入)	VGA@ 4 x 30/25 fps		VGA@ 8 x 30/25 fps		
	輸出		1 HDMI (Max. 3840 x 2160) with Audio and 1 VGA (Max. 1920x1080) 1 Main BNC				
聲音	輸入		4 RCA				1 RCA
	壓縮		Audio Codec : G726 · G711 u/a IMA_ADPCM Sample Rate : 8k, Channel 1 Depth 16				
系統	輸出		1 RCA				
	操作系統		Embedded Linux OS				
	SATA裝置		Max. 1 x SATA Device (HDD x 1)				
	外部硬碟		N/A				
	輸入點偵測 /繼電器		N/A	Alarm-in x 4 Relay-out x 1	N/A	Alarm-in x 8 Relay-out x 1	N/A
	IO 介面		RS-485				
	USB 2.0 埠		USB2.0 X2				
	尺寸		280(w)x51(h)x203(d)				
	電壓		12V 2A, 24W				12V 3A, 36W
	顯示	分割畫面		1,4, SEQ.		1,4, 9, SEQ.	
自動跳台		Switching time : 1 ~ 99 sec					
模式		Zoom, Auto SEQ.					
錄影	壓縮格式		H.265 Main Profile				
	畫面解析度		2592 x 1944 ,2592 x 1520, 2018 x 1524 ,1920 x 1080, 1280 x 720; 944 x 480 ,704 x 480, 352 x 240 (NTSC) / 944 x 576 ,704 x 576, 352 x 288 (PAL)				
	網路解析度		640 x 360 / 352 x 240, 176 x 120 (NTSC) / 352 x 288, 176 x 144 (PAL)				
	畫質調整		10~100 levels for adjustment				
	模式		Continuous, Event, Schedule				
	錄音速度		TVI/AHD/CVI : 5MP, 4MP@15/12 fps, 3MP@15/12 fps, 1080P@30/25 fps, 720P@30/25 fps, 960H/D1@30/25 fps				
	錄影前提示警告		1 ~ 5 SEC				
	錄影後提示警告		1 ~ 100 SEC				
回放	搜尋模式		Date/time, Event				
	放大		*Digital (x2 ~ x5)				
網路	網路速度		10/100 Ethernet				
	網路協定		TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS				
	OS支援		Windows 7 & 8, Mac OS X				
	遠端控制軟體		SoCatch, IE Browser, iCMS Pro				
	使用者帳戶		1 Admin + 10 Users				
	行動裝置支援		iOS & Android				
備份	外接介面		USB or SATA				
	聲音備份		YES				
	備份界面		Network, ext. USB flash device , SATA optical DVD...etc.				
警報	移動偵測		Sensitivity: 100 levels for each channel Area: Programmable individually				
	事件日誌		Up to the 10000 events (Sensor, Motion, Video loss, Power on, Remote login, Logout, HDD error, HDD full)				
功能控制	多國語言		Supported				
	攝影機標題		Multi-Language				
	USB滑鼠		YES				
	觸控螢幕		-				
	搖控控制		IR Remote Control				
	系統控制		USB Flash Drive, iWatch DVR				
一般	Pan/ Tilt/ Zoom 控制		Control From RS485 Interface (Pelco P, Pelco D, Samsung, LG, LiLin)				
	操作溫度		0°C ~ +55°C (32°F ~ 131°F)				
	操作濕度		10%~80%				

All specifications are subject to change without notice.



TEL : 886-2-5550-6660 FAX : 886-2-2452-7815
台北市南港區三重路19-13號3樓



www.icatchinc.com